

SPONSORED BY: MAYOR PRO TEM CLYNE

COUNCILMAN'S RESOLUTION

RESOLUTION NO.

No. CR-63
Series of 2013

Series of 2013

A RESOLUTION ADOPTING THE CITY OF NORTHGLENN GUN SAFE REBATE PROGRAM

BE IT RESOLVED BY THE CITY COUNCIL OF THE CITY OF NORTHGLENN, COLORADO, THAT:

Section 1. The City Council hereby adopts the City of Northglenn Gun Safe Rebate Program as follows:

A. The City shall reimburse any resident of the City as follows to reimburse the cost of a gun safe that meets the requirements set forth in **Exhibit A**, attached hereto and incorporated herein by this reference:

i. Up to twenty-five percent (25%) of the cost of such a gun safe up to a maximum rebate amount of \$500; or

ii. Up to thirty percent (30%) of the cost of such a gun safe up to a maximum rebate amount of \$525 if the gun safe is purchased from a City of Northglenn business.

B. City staff is hereby directed to implement a process to facilitate the use of the City of Northglenn Gun Safe Rebate Program (the "Program"), which process shall include mechanisms to assure that the Program is limited to City residents who purchase a new gun safe that meets the standards set forth in **Exhibit A**.

Section 2. The adoption the Program is subject to the appropriation and availability of funds to reimburse residents for purchases of gun safes in accordance with the Program.

DATED at Northglenn, Colorado, this ____ day of _____, 2013.

JOYCE DOWNING
Mayor

ATTEST:

APPROVED AS TO FORM:

JOHANNA SMALL, CMC
City Clerk

COREY Y. HOFFMANN
City Attorney

Exhibit A

City of Northglenn Gun Safe Rebate Program Requirements

Gun safes for which reimbursement is available pursuant to the City of Northglenn Gun Safe Rebate Program shall meet the following minimum requirements:

1. Shall be able to fully contain firearms and provide for their secure storage;
2. Shall have a locking system consisting of at minimum a mechanical or electronic combination lock. The mechanical or electronic combination lock utilized by the safe shall have at least 10,000 possible combinations consisting of a minimum three numbers, letters, or symbols. The lock shall be protected by a case-hardened (Rc 60+) drill-resistant steel plate, or drill-resistant material of equivalent strength;
3. Boltwork shall consist of a minimum of three steel locking bolts of at least ½ inch thickness that intrude from the door of the safe into the body of the safe or from the body of the safe into the door of the safe, which are operated by a separate handle and secured by the lock;
4. Shall be capable of repeated use. The exterior walls shall be constructed of a minimum 12-gauge thick steel for a single-walled safe, or the sum of the steel walls shall add up to at least .100 inches for safes with two walls. Doors shall be constructed of a minimum of two layers of 12-gauge steel, or one layer of 7-gauge steel compound construction; and
5. Door hinges shall be protected to prevent the removal of the door. Protective features include, but are not limited to: hinges not exposed to the outside, interlocking door designs, dead bars, jeweler's lugs and active or inactive locking bolts.

OR

1. Is listed as an Underwriters Laboratories Residential Security Container;
2. Is able to fully contain firearms;
3. Provides for the secure storage of firearms; and
4. Underwriters Laboratories Residential Security Container standards include residential storage containers that are able to withstand five minutes of consistent prying, drilling, punching, hammering and tampering attacks by the UL technicians. The steel constructed doors measure between 10 to 12 gauge in thickness.